

# TECHNICAL FEATURES

## CEPPO

*Light 6 mm*

### TECHNICAL FEATURES UNGLAZED PORCELAIN STONEWARE

CONFORMING TO EUROPEAN STANDARDS EN 14411 ISO 13006 APP. G (GROUP BIA UGL  $E_b \leq 0,5\%$ )

CARATTERISTICHE TECNICHE GRÈS PORCELLANATO NON SMALTATO Conformi a Norme Europee EN 14411 ISO 13006 App. G (Gruppo Bia UGL  $E_b \leq 0,5\%$ )

TECHNISCHE EIGENSCHAFTEN UNGLASIERTES FEINSTEINZEUG Gemäß den Europäischen Normen EN 14411 ISO 13006 App. G (Gruppe Bia UGL  $E_b \leq 0,5\%$ )

CARACTERISTIQUES TECHNIQUES GRÈS CÉRAME FIN NON ÉMAILLÉ Conformes aux Normes Européennes EN 14411 ISO 13006 App. G (Groupe Bia UGL  $E_b \leq 0,5\%$ )



sizes

**EN ISO 10545-2**

compliant



water  
absorption

**EN ISO 10545-3**

compliant



breaking  
strenght

**EN ISO 10545-4**

compliant  
 $\geq 35 \text{ N/mm}^2$



abrasion  
resistance

**EN ISO 10545-6**

$< 175 \text{ mm}^3$



thermal expansion  
coefficient

**EN ISO 10545-8**

$\leq 9 \text{ MK-1}$



thermal shock  
resistance

**EN ISO 10545-9**

resistant



frost  
resistance

**EN ISO 10545-12**

resistant



chemicals  
resistance

**EN ISO 10545-13**

from ULA to ULB  
from UHA to UHB  
UA



stains  
resistance

**EN ISO 10545-14**

class 5



colors  
resistance to light

**DIN 51094**

no alteration  
after testing



friction  
coefficient

**DIN 51130**  
**ANSI A 137.1 (DCOF)**

R10 matt  
 $> 0,42$